



St. Stogovo 13 A 1000 Skopje, Macedonia
Phone: 389 2 3124 322 Fax: 3126 920 E: mail@euromakkontrol.com



EUROMAK-KONTROL INSPECTION DEPARTMENT QUALITY SUPERINTENDENCE CORPORATION

QUALITY CERTIFICATE No. 58-1/25

Skopje, 30.04.2025

I. GENERAL INFORMATION

- Product name:** Hydrostop Liquid Rubber, liquid rubber - transparent waterproofing
- Client:** Company for production, trade, services and transport NILEGO GROUP DOOEL import-export Kumanovo
- Date and place of inspection:** 15.04-30.04.2025 Laboratory of Euromak Kontrol-Skopje (Report No. XIV-04-25/69)
- Conditions of inspection:** After submitted sample
- Technical documentation** The Law on Chemicals ("Official Gazette of the Republic of Macedonia" No. 145/10), The Rulebook on the conditions regarding the health safety of items for general use that can be placed on the market (Official Gazette of the SFRY 26/83 and 50/89), The Law on General Product Safety (Official Gazette of the Republic of Macedonia No. 302/20, 3/25).

II. SUBJECT TO INSPECTION

Qualitative inspection: Organoleptic, physical-chemical analysis of Hydrostop Liquid Rubber, liquid rubber - transparent waterproofing.

III. INSPECTION REPORT

Organoleptic analysis	Results
Appearance	Thick mixture
Color	White
Odor	Characteristic of the product
Packing	Plastic packaging of 800 g

3.1 Physical and chemical analysis:

Parameters	Declared values	Results
Solubility in water	/	Total
pH (1% solution)	/	8,38
Total dry residue at 105°C	/	86,3%
Volatile components 105°C	/	13,7%
Specific gravity	/	1,031 g/cm ³

3.2 Manufacturer Specification:

Polymer
Water
Antifoam

IV. USE OF THE PRODUCT

Hydrostop Liquid Rubber, liquid rubber - transparent waterproofing is a special sealing emulsion for walls, flat roofs, basements, bathrooms, foundations, pools, fountains, balconies and any other concrete surfaces. The film obtained with liquid rubber transparent is very elastic, durable, waterproof and decorative at the same time. It can be used indoors and outdoors, on old and new surfaces. It is ideal for surfaces with cracks due to its elasticity. It is also resistant to the creation of new cracks on an already covered surface. It is applied to: plaster, bricks, natural concrete, plaster, glass, wood, plywood, metal, etc. It can be applied before gluing ceramic tiles as well as on them. The film formed by liquid rubber transparent is completely resistant to external influences over a long period of time. Surfaces coated with liquid rubber transparent are flat, without joints and joints. The product can be pigmented.

V. PRODUCT USE

The substrate should be clean, dry, dust-free and degreased. First, apply Polygrund 1k elastic substrate. The transparent liquid rubber is applied on top of it. When applying the first coat, it can be diluted with water up to 15%. For the second and third coats, it is applied undiluted. It is applied with a pointed roller or brush (for smaller surfaces) or by spraying (for larger surfaces). Each subsequent coat, the liquid rubber is applied after the previous one has dried. The drying time is several hours depending on the weather conditions. It is applied exclusively on a dry surface.

NOTE: Until it dries, it must not come into contact with water or other liquids. It is applied exclusively at temperatures above 5°C and it is not recommended to work at temperatures above 35°C. 2-3 coats are applied depending on the surface and need. If necessary, it can be reinforced with glass mesh or microfiber fibers on edges and corners where reinforcement is needed. Tools and hands are washed with water.

VI. PACKAGING AND MARKING

The delivered sample is packed in a single original plastic packaging. In accordance with the provisions of the Law on Chemicals ("Official Gazette of the Republic of Macedonia" No. 145/10), the declaration of the product contains: **Hydrostop Liquid Rubber, liquid rubber - transparent waterproofing**, name and trademark, address and telephone number of the legal entity responsible for placing on the market, address, e-mail address and telephone number of the person from whom the list of data on the ingredients can be obtained, as well as the content of the product and instructions for use and special warnings.

VII. STORAGE AND PRESERVATION

Store in rooms with a temperature of 5 to 35 °C. It is not recommended to store it for a long time in direct sunlight. The product must not be frozen!

VIII. SAFETY MEASURES

8.1 Health hazard

In case of oral consumption of the preparation, it is necessary to rinse the stomach with a large amount of plain water and immediately seek professional medical help. In case of contact of the preparation with eyes, it is necessary to rinse with a strong stream of water for at least 15 minutes, and in the meantime seek medical help. It is recommended to use personal protective equipment when working.

IX. CONCLUSION

Based on the analysis of the physicochemical characteristics and the results obtained, it is concluded that the sample in question, **Hydrostop Liquid Rubber, liquid rubber - transparent waterproofing**, meets the requirements in accordance with the Law on Chemicals ("Official Gazette of the Republic of Macedonia" No. 145/10), the Rulebook on the conditions regarding the health safety of objects for general use (Official Gazette of the Republic of Macedonia 26/83 and 50/89), and the Law on Product Safety (Official Gazette of the Republic of Macedonia No. 33/06, 63/07, 24/11, 51/11, 148/11, 164/13, 152/15) and can be put into use.

Inspector – Teodora Vrazalkovska

creates

Senior Inspector – Suzana Temelkoska

controls

Technical manager – Suzana Temelkoska

approves

NOTE: The inspection certificate refers exclusively to the conditions and place at the time the inspection was performed. Reproduction of this Inspection Report is not permitted, only with the approval of the inspection sponsor and the inspection body.

This inspection has been carried out to the best of our knowledge and conscience and this certificate does not absolve the seller and the buyer from their contractual responsibilities. In case of quality superintendence or inspection of goods we are responsible in accordance with the deed contract, in case of taking over of goods in accordance with principles of power of attorney, while for weight and quality quarantine transactions we are responsible in accordance with the stipulations of contracts concluded relative to such transactions